

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 2

CLAIMS AMENDMENTS

RECEIVED
CENTRAL FAX CENTER
MAY - 7 2008

1-16 (canceled).

17 (currently amended). ~~A ~~the~~ method ~~of claim 16,~~ for~~
controlling oxidative degradation of an oleaginous liquid
substance in a generally enclosed, vented space in a working
machine, which comprises providing said working machine having
said space; providing said oleaginous liquid substance; and
blanketing said oleaginous liquid substance in said space with an
inert gas blanket to control oxidative degradation of said
oleaginous liquid substance, wherein said oleaginous liquid
substance is selected from the group consisting of an oil and a
transmission fluid, and said machine is selected from the group
consisting of a transmission box, a gear box that is not a
transmission box, and an internal combustion engine having a
crankcase for holding a supply of lubricant and wherein said
oleaginous substance is present in the crankcase as the
lubricant.

18 (canceled).

19 (previously presented). The method of claim 17, wherein
said inert gas of said inert gas blanket is provided from
separation of air with a membrane-containing device.

20 (previously presented). The method of claim 19, wherein
said oleaginous liquid substance is an engine oil; said machine
is said internal combustion engine, and it is necessary to change
the engine oil of the crankcase owing to the control of oxidative
degradation of the engine oil, and the engine oil is changed,
only after at least twenty thousand miles of use in said internal
combustion engine, whereas, without the presence of said inert

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 3

gas blanket, the engine oil would present properties of needing to be changed after a few thousand miles of use in said internal combustion engine in comparison to the engine oil protected by said blanket after said at least twenty thousand miles.

21-38 (canceled).

39 (previously presented). The method of claim 17, wherein said working machine is selected from the group consisting of said transmission box and said gear box:

40-42 (canceled).

43 (previously presented). The method of claim 39, wherein said inert gas of said inert gas blanket is provided from separation of air with a membrane-containing device.

44-45 (canceled).

46 (previously presented). The method of claim 19, wherein gas enriched with nitrogen provides said inert gas blanket, and by-product gas enriched with oxygen is delivered for consumption to a location selected from the group consisting of a part of the machine other than said enclosed space, and a passenger cabin space.

47-49 (canceled).

50 (previously presented). A method for controlling oxidative degradation of an engine oil in a crankcase of an internal combustion engine, which comprises providing said engine; providing said engine oil to said crankcase; and blanketing said engine oil in said crankcase with an inert gas blanket to control oxidative degradation of said engine oil.

51 (previously presented). The method of claim 50, wherein it is necessary to change the engine oil of said crankcase owing

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 4

to the control of oxidative degradation of said engine oil, and said engine oil is changed, only after at least twenty thousand miles of use in said internal combustion engine, whereas, without the presence of said inert gas blanket, the engine oil would present properties of needing to be changed after a few thousand miles of use in said internal combustion engine in comparison to the engine oil protected by said blanket after said at least twenty thousand miles.

52 (previously presented). The method of claim 51, wherein it is necessary to change the engine oil of said crankcase owing to the control of oxidative degradation of said engine oil, and said engine oil is changed, only after at least fifty thousand miles of use in said internal combustion engine, whereas, without the presence of said inert gas blanket, the engine oil would present properties of needing to be changed after a few thousand miles of use in said internal combustion engine in comparison to the engine oil protected by said blanket after said at least fifty thousand miles.

53 (previously presented). The method of claim 52, wherein said inert gas of said inert gas blanket is provided from separation of air with a membrane-containing device.

54-60 (canceled).

61 (previously presented). A method for controlling oxidative degradation of an engine oil in a crankcase of an internal combustion engine and delivering oxygen to a place away from said crankcase, which comprises providing said engine; providing said engine oil to said crankcase; providing a means for supplying an inert gas blanket of a gas enriched with

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 5

nitrogen in comparison to air, which separates nitrogen and oxygen from the air to provide said inert gas blanket and provide a by-product gas enriched in oxygen; providing a means for directing said inert gas blanket to said crankcase, and blanketing said engine oil in said crankcase with said inert gas blanket to control oxidative degradation of said engine oil; and providing a means for directing said by-product gas to the place away from said crankcase.

62 (previously presented). The method of claim 61, wherein the place away from said crankcase to which said by-product gas is directed is selected from the group consisting of a fuel injector assembly, and an air cleaner assembly for intake into a carburetor.

63 (previously presented). The method of claim 61, wherein the place away from said crankcase to which said by-product gas is directed is a catalytic converter.

64 (previously presented). A method for controlling oxidative degradation of an engine oil in a crankcase of an internal combustion engine and delivering oxygen to a place away from said crankcase, which comprises providing said engine; providing said engine oil to said crankcase; providing a membrane-containing device for separation of air to supply an inert gas blanket of a gas enriched with nitrogen in comparison to air, which separates nitrogen and oxygen from the air to provide said inert gas blanket and provide a by-product gas enriched in oxygen; providing a means for directing said inert gas blanket to said crankcase; under overpressure conditions, blanketing said engine oil in said crankcase with said inert gas

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 6

blanket to control oxidative degradation of said engine oil; and providing a means for directing said by-product gas to the place away from said crankcase.

65 (previously presented). A method for controlling oxidative degradation of a transmission fluid in a transmission and delivering oxygen to a place away from said transmission, which comprises providing said transmission; providing said transmission fluid to said transmission; providing a means for supplying an inert gas blanket of a gas enriched with nitrogen in comparison to air, which separates nitrogen and oxygen from the air to provide said inert gas blanket and provide a by-product gas enriched in oxygen; providing a means for directing said inert gas blanket to said transmission, and blanketing said transmission fluid in said transmission with said inert gas blanket to control oxidative degradation of said transmission fluid; and providing a means for directing said by-product gas to the place away from said transmission.

66 (previously presented). The method of claim 65, wherein the place away from said transmission to which said by-product gas is directed is selected from the group consisting of a fuel injector assembly, and an air cleaner assembly for intake into a carburetor.

67 (previously presented). The method of claim 65, wherein the place away from said transmission to which said by-product gas is directed is a catalytic converter.

68 (canceled).

69 (new). A method for controlling oxidative degradation of an oleaginous liquid substance in a generally enclosed, vented

Hall et al., 09/172577

Amdt. after Dec'ns ..., p. 7

space in a working machine, which comprises providing said working machine having said space; providing said oleaginous liquid substance; and blanketing said oleaginous liquid substance in said space with an inert gas blanket to control oxidative degradation of said oleaginous liquid substance, wherein said inert gas of said inert gas blanket is provided from separation of air with a membrane-containing device.

70 (new). The method of claim 69, wherein gas enriched with nitrogen provides said inert gas blanket, and by-product gas enriched with oxygen is delivered for consumption to a location selected from the group consisting of a part of the machine other than said enclosed space, and a passenger cabin space.